

## *PATENTED STORMWATER CURB INLET GUARD*

Protected by U.S. Patents #5,702,595 & #6,017,166

### SPECS AND DETAILS:

- Standard: 4' long, Sea water-resistant aluminum, 1 3/8" hole openings, .040 thickness
- Can be custom fabricated: per engineering specs, per inlet opening size or shape (imperfect or curved openings), other thicknesses available
- Installed using Tapcon 1/4" x 1 1/4" concrete anchors drilled directly through the Guard top lip into the top of the inlet box/lid, and through the bottom lip of the Guard into the concrete curb base
- Sediment/Erosion Control Guard uses filter fabric per customer specs wrapped and attached to the curb box opening
- Petro/Chemical Guard is fabricated with a 3' sq box into which a sorbent boom is inserted, a Guard face plate to cover and protect boom is attached using zip ties for easy changing of soiled boom
- Guard attaches to the face of the curb inlet opening, outside the curb box
- Street sweepers with nylon brushes do not affect the integrity of the Permanent Guard
- No moving parts to jam or malfunction
- No Confined Space Certification required to install or maintain
- Emblem, Seal, decal, or signage can be etched or secured to the top or face of Guard. Additional costs may apply.
- Amy's guarantees the installation of our Guards for one year. This guarantee does not include breakage, damage, or theft.
- Fabricated, exclusively sold and installed by Amy's Contracting Services, a DC Metro area Woman Owned Business, MDOT certified MBE.

